



External GSM Antenna

for Datek Light Control System

Ordering information

101369 - External GSM antenna

Technical information:

Antenne GSM/2G/3G 824-960/1720-2170MHz 2m IP67 24mm SMA
Producer Part no. GSM-11A
Frequency 3G/GSM - 824-960/1710-2170MHz

Features

Low profile puck antenna
Fully waterproof when mounted - IP67 waterproof
For indoor or outdoor use - UV resistant
Groundplane independent
SMA-male connector

Electrical

Type: Screw Mount (Puck)
Frequency: GSM-11A: 3G/GSM - 824-960/1710-2170MHz
VSWR: ≤ 2.0
Impedance: 50ohms
Gain: 0-3dBi
Radiation: Omni
Electrical wave: 1/2
Polarization: Vertical
Max Power: 10W

Mechanical

Antenna Size: 54.7 x 23.3mm
Operating temp.: -30 to +70 degree
Storage temp.: -35 to +75 degree

Mounting

Screw Mount

Cable and connector

RG174/u low loss cable 2meter - SMA male

Made in Taiwan
Compliant with RoHS Directive

www.datek.no / Tlf: 920 38 000

datek^{CITY}

Subject to change without notice
2020-09-02-v1 © Datek Light Control AS